



1/14






FIG. 1

2/14



TYPICAL XRD PATTERN FROM A
SURFACTANT-TEMPLATED MATERIAL.


FIG. 2



TYPICAL PORE SIZE DISTRIBUTION FROM
A SURFACTANT-TEMPLATED MATERIAL.

FIG. 3

3/14



IN EXAMPLE 1 - PRODUCTION OF CeO₂. TEMPERATURE HISTORY.

FIG. 4

4/14






FIG. 5



5/14



XRD TRACES FROM CeO_2 , $\text{Ce}_{0.65}\text{Sm}_{0.4}\text{O}_x$,
 $\text{Ce}_{0.65}\text{Sm}_{0.2}\text{Cu}_{0.15}\text{O}_x$, $\text{Ce}_{0.6}\text{Zr}_{0.2}\text{Sm}_{0.1}\text{Cu}_{0.1}\text{O}_x$

FIG. 6(a)



6/14



XRD TRACES FROM CeO_2 , $\text{Ce}_{0.6}\text{Sm}_{0.4}\text{O}_x$,
 $\text{Ce}_{0.65}\text{Sm}_{0.2}\text{Cu}_{0.15}\text{O}_x$, $\text{Ce}_{0.6}\text{Zr}_{0.2}\text{Sm}_{0.1}\text{Cu}_{0.1}\text{O}_x$

FIG. 6(b)

7/14



SAXS DATA FOR GELS COMPRISED OF CERIUM NITRATE SOLUTIONS & BRIJ 35, BRIJ 56 & PLURONIC F127 SURFACTANTS. ALSO SHOWN IS SAXS DATA FROM THE POWDERS PRODUCED FROM THESE GELS

FIG. 7(a)

8/14





FIG. 7(b)

9/14






FIG. 7(c)

10/14



*PORE SIZE DISTRIBUTION FROM CeO_2 POWDER MADE
USING BRIJ 35 SURFACTANT (SURFACE AREA = $253 \text{ m}^2/\text{g}$)*

FIG. 8

11/14

*COMPARISON OF ABOVE DATA WITH A TYPICAL PORE
SIZE DISTRIBUTION FROM A SURFACTANT-TEMPLATED
MATERIAL*





FIG. 9






FIG. 10

13/14



XRD TRACE FROM $\text{La}_{0.6}\text{Ca}_{0.2}\text{Nd}_{0.2}\text{Mn}_{0.9}\text{Ni}_{0.1}\text{O}_3$


FIG. 11



SAXS DATA FROM $\text{La}_{0.6}\text{Ca}_{0.2}\text{Nd}_{0.2}\text{Mn}_{0.9}\text{Ni}_{0.1}\text{O}_3$

FIG. 12

14/14



HEAT TREATMENT SCHEDULES FOR CeO₂ MATERIALS IN "EXPERIMENTS IN STEP 2:
MIXING THE SOLUTION WITH SURFACTANT".

FIG. 13